

WOLF OE LEVELTECH 5W30 MS-F

03/05/2025
75623

This is a full synthetic lubricant based on carefully selected very high quality base oils, especially developed for the requirements of Ford WSS-M2C913-C/D specifications. It is characterized by significantly improved lubricating properties and provides Fuel Economy (>3%). This oil replaces the M2C-913-A/B specifications. This product may not be available in your region. Please, consult your local sales contact for more information.

APLICAȚII

It is mandatory for all Ford models (gasoline and diesel, also those with particulate filter) from 2009 onwards. It's also required for the vehicles equipped with the 2,2 Duratorq TDCI engines and is fully backwards compatible with all current Ford diesel engines, with the exception of the models which are equipped with pump injectors (Galaxy I en II) and Ford KA (diesel and gasoline from 2009).

CARACTERISTICI

Fuel economy: superior fuel economy and CO2 reduction
Total engine protection: performance in keeping the engine clean
Pornire la rece: Fluiditate excelentă la temperaturi scăzute

SPECIFICAȚII

ACEA	A1/B1-12	FORD	WSS-M2C913-C/D
ACEA	A5/B5	JAGUAR-LAND ROVER	STJLR.03.5003
API	SN/CF	RENAULT	RN 0700
ILSAC	GF-5	VW	VWC 53036

Test	Metoda	Unitate	Rezultate medii
Densitate la 15°C	ASTM D4052	g/ml	0.854
Viscozitate cinematică la 40°C	ASTM D445	mm²/s	63.8
Viscozitate cinematică la 100°C	ASTM D445	mm²/s	11.0
Indice de viscozitate	ASTM D2270		166
B.N. (metodă HClO4)	ASTM D2896	mg KOH/g	10.4
Punct de curgere	ASTM D6892	°C	-42
Punct de aprindere COC	ASTM D92	°C	224

Ne rezervăm dreptul de a aduce modificări caracteristicilor generale ale produselor noastre, pentru a permite clienților noștri să beneficieze de cele mai recente evoluții tehnice.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

