

WOLF ESSENTIAL SN/CF C3 5W40 PI

14/04/2025
75608

This full synthetic engine oil meets the core requirements of ACEA and API for passenger cars. It keeps soot particles dispersed and prevents the formation of piston deposits.

APLICAȚII

This engine oil is recommended for direct injection diesel engines, including common rail direct fuel injection systems with or without aftertreatment system.

CARACTERISTICI

Aftertreatment protection: full aftertreatment system protection
Total engine protection: outstanding engine cleanliness and durability

SPECIFICAȚII

ACEA	C3	MB	229.51
API	SN/CF	VW	505 00
MB	229.31	VW	505 01

Test	Metoda	Unitate	Rezultate medii
Densitate la 15°C	ASTM D4052	g/ml	0.849
Viscozitate cinematică la 40°C	ASTM D445	mm ² /s	80.5
Viscozitate cinematică la 100°C	ASTM D445	mm ² /s	13.8
Indice de viscozitate	ASTM D2270		177
B.N. (metodă HClO ₄)	ASTM D2896	mg KOH/g	6.8
Punct de curgere	ASTM D6892	°C	-42

Ne rezervăm dreptul de a aduce modificări caracteristicilor generale ale produselor noastre, pentru a permite clienților noștri să beneficieze de cele mai recente evoluții tehnice.